



▶ MAJOR ADVANTAGES

- Extended service life:
 - > high coating thickness
 - > abrasion resistance
- **Multi-application product**
- Complies to standard DIN 18204
- Long-term tension prevents bagging
- No elongation within the warp and weft

TECHNICAL SPECIFICATIONS

	Précontraint 832	Standards
Yarn	2 x 1100 dtex PES HT	TERSUISSE
Weight	850 g/m ²	EN ISO 2286-2
Width	180 cm / 270 cm	
Standard format length/jumbo rolls*	± 50 lm/± 300 lm	
Tensile strength (warp/weft)	400/400 daN/5 cm	EN ISO 1421
Tear strength (warp/weft)	50/50 daN	DIN 53.363
Adhesion	11/11 daN/5 cm	EN ISO 2411
Elongation under load (warp/weft)	<1% / <1%	EN 15619
Finish	Varnish both sides	
Flame retardancy	M2/NFP 92-507 • Method 2/NFPA 701 • CSFM T19 • B1/DIN 4102-1 • BS 7837 • Schwerbrennbar Q1-Tr1/ONORM A 3800 • VKF 5.3/SN 198898 • SIS 650082 (ETA) • G1/GOST 30244-94	
Euroclass	B-s2, d0/EN 13501-1	
Cold resistance	- 30°C	ISO 4675
Heat resistance	+ 70°C	
Quality management system		ISO 9001

COLOURS & REFERENCES

832-8100 270 cm Low wick thread treatment	832-1071 270 cm RAL 7038	832-1070 270 cm RAL 7037	832-50309 270 cm RAL 7015	832-1075 180 cm RAL 9005
832-1053 270 cm RAL 5015	832-1051 270 cm RAL 5002			